




KTC-LAGERSCHRANK

Zur Lagerung von wassergefährdenden Flüssigkeiten

- ◆ Abschließbarer Wetterschutzaufbau - dadurch zur Lagerung im Freien geeignet
- ◆ Auffangwanne aus 3 mm Stahlblech, entsprechend AwSV - **Ü-Zeichen gemäß StawaR**
- ◆ Korrosionsschutz durch Grundierung und Lackierung der Auffangwanne
- ◆ Wetterschutzaufbau aus Stahlblech verzinkt
- ◆ Auffangvolumen: 1.000 Liter
- ◆ Belastung: 1.500 kg/m²
- ◆ 100 mm Bodenfreiheit für Staplertransport
- ◆ Entlüftungsöffnungen in der Seitenwand
- ◆ Inkl. Abfüllbock
- ◆ Dokumentenablage im Türfach serienmäßig



Lüftungsöffnungen in den Seitenwänden



WSP-1SKKS-D/KTC,
Artikel-Nr. P21-2485-A

Typenbezeichnung	WSP-1SKKS-D/KTC
Außenmaße B x T x H in mm	1320 x 1370 x 2380
Innenmaße B x T in mm	1285 x 1285
Fachhöhe in mm	1580
Gewicht in kg	450
Artikel-Nr., verzinkt	P21-2485-A

ABLUFVENTILATOR-SET FÜR KTC-LAGERSCHRANK

Zur Lagerung entzündbarer Flüssigkeiten gem. TRGS 510 als Zubehör erhältlich:

- ◆ Zur vorschriftsgemäßen Absaugung oberhalb der Bodenwanne
- ◆ Geeignet zur aktiven und passiven Lagerung entzündbarer Flüssigkeiten
- ◆ Abluftventilator-Set verdrahtet bis Schaltkasten
- ◆ Bauseitige Leistung: Zuleitung 230 V



Schaltkasten, inkl. Verdrahtung



Abluftventilator-Set,
Artikel-Nr. P21-2486-A





SICHERHEITSLAGERHÄUSER KTC

Spezial-Containeraufbau

- ◆ Hergestellt aus speziell profiliertem, verzinktem Stahlblech
- ◆ Verstärkte Dach- und Bodenrahmenprofile
- ◆ Flüssigkeitseinleitbleche umlaufend, außer Türbereich
- ◆ Integrierte, wettergeschützte Lüftungsöffnungen in der Tür und gegenüberliegender Rückwand
- ◆ **SLH 2 x 2/KTC und SLH-NB 2 x 2/KTC Kranösen serienmäßig**
- ◆ Anlieferung erfolgt im montiertem Zustand

Auffangwanne mit Gitterrostauflage

- ◆ Aus 3 mm Stahlblech, **feuerverzinkt**, entsprechend AwSV - **Ü-Zeichen gemäß StawaR**
- ◆ Belastung 1500 kg/m², höhere Belastung auf Anfrage
- ◆ Unterfahrhöhe 100 mm

2-flügelige verzinkte Stahltür

- ◆ Mit Lüftungsschlitzen
- ◆ Abschließbar mit Sicherheitsschloss
- ◆ Türbreite:
 - SLH 2 x 2/KTC und SLH-NB 2 x 2/KTC: 1950 mm
 - SLH 3 x 2/KTC und SLH-NB 3 x 2/KTC: 2650 mm
 diese Türbreite erleichtert das Einbringen von 2 KTC/IBC



Thermoisolierte Version zur frostfreien Lagerung auf Anfrage!

Zugelassen zur Lagerung von:

- ◆ Typ SLH 2 x 2/KTC und SLH 3 x 2/KTC
 - Zugelassen zur Lagerung wassergefährdender Medien
- ◆ Typ SLH-NB 2 x 2/KTC und SLH-NB 3 x 2/KTC
 - Zugelassen zur passiven Lagerung entzündbarer Medien
 - Durch umlaufende Lüftungsöffnungen direkt über der Auffangwanne, Lüftungsöffnungen im oberen Bereich von Rückwand und Tür, wird der gesetzlich geforderte mindestens 0,4-fache Luftwechsel erreicht.
 - Inkl. Erdungsanschluss zur Vermeidung gefährlicher elektrostatischer Aufladung



Zubehör finden Sie auf Seite 172/173!



SLH 3 x 2 KTC, verzinkt, Artikel-Nr. H61-2143-B



für wassergefährdende Medien



für entzündbare Medien (passive Lagerung)

Zugelassen	für wassergefährdende Medien		für entzündbare Medien (passive Lagerung)	
Typenbezeichnung	SLH 2 x 2/KTC	SLH 3 x 2/KTC	SLH-NB 2 x 2/KTC	SLH-NB 3 x 2/KTC
Außenmaße B x T x H in mm	2075 x 2075 x 2480	3075 x 2075 x 2385	2075 x 2075 x 2665	3075 x 2075 x 2565
Innenmaße B x T x H in mm	1980 x 1980 x 1970	2980 x 1980 x 1970	1980 x 1980 x 2150	2980 x 1980 x 2150
Türbreite in mm	1950	2650	1950	2650
Auffangvolumen in Liter	1000	1000	1000	1000
Kapazität	1 KTC/IBC	2 KTC/IBC	1 KTC/IBC	2 KTC/IBC
Artikel-Nr., verzinkt	H61-2116-B	H61-2143-B	H63-1116-A	H63-1112-A
Artikel-Nr., verzinkt und außen lackiert	H61-6116-B	H61-6143-B	H63-2116-A	H63-2112-A



SUMP TRAY MADE FROM STEEL WITH SUPERSTRUCTURE




Explanations see practical informations on page 9 and 90!

KTC-STORAGE CABINET

For the storage of water-endangering liquids

- ◆ Lockable weather protection superstructure - therefore, suitable for outdoor storage
- ◆ Sump pallet made from 3 mm sheet steel as per AwSV - **Ü-sign according to StawaR**
- ◆ Corrosion protection by priming and painting of the sump pallet
- ◆ Weather protection superstructure made from galvanized sheet steel
- ◆ Sump capacity: 1.000 liters
- ◆ Max. load: 1.500 kg/m²
- ◆ 100 mm ground clearance for transport with forklift truck
- ◆ Ventilation slots in the sidewalls
- ◆ Incl. filling stand
- ◆ Compartment for documents in the doors as standard



Ventilation slots in the side walls



WSP-1SKKS-D/KTC,
Article no. P21-2485-A

Model	WSP-1SKKS-D/KTC
External dimensions W x D x H (mm)	1320 x 1370 x 2380
Internal dimensions W x D x H (mm)	1285 x 1285
Compartment height (mm)	1580
Weight (kg)	450
Article no., galvanized	P21-2485-A

EXHAUST FAN SET FOR KTC-STORAGE CABINET

For the storage of flammable liquids according to TRGS 510 available as accessory:

- ◆ For the correct suction above the base sump tray
- ◆ Suitable for active and passive storage of flammable liquids
- ◆ Exhaust fan set wired up to switch box
- ◆ Service provided by the customer: Power supply 230 V



Switch box, incl. wiring



Exhaust fan set,
Article no. P21-2486-A





SAFETY STOREHOUSES FOR KTC

Special container superstructure

- ◆ Made from especially profiled and galvanized sheet steel
- ◆ Reinforced roof and frame profiles
- ◆ Circumferential splash protection made from sheet steel, except door area
- ◆ Weather-protected venting slots in the door and opposite door
- ◆ **SLH 2 x 2/KTC and SLH-NB 2 x 2/KTC lifting attachments as standard**
- ◆ Mounted delivery

Sump tray with grid

- ◆ Made from 3 mm sheet steel, **fire-galvanized**, as per AwSV - **Ü-sign according to StawaR**
- ◆ Max. load 1500 kg/m², higher load on request
- ◆ Ground clearance 100 mm

2-winged galvanized steel door

- ◆ With venting slots
- ◆ Safety lock
- ◆ Door width:
 - SLH 2 x 2/KTC and SLH-NB 2 x 2/KTC: 1950 mm
 - SLH 3 x 2/KTC and SLH-NB 3 x 2/KTC: 2650 mm
 increased door width simplifies the loading of 2 KTC/IBC



Thermal insulated version for frostfree storage on request!

Approved for the storage of:

- ◆ Type SLH 2 x 2/KTC and SLH 3 x 2/KTC
 - Approved for the storage of water-endangering media
- ◆ Type SLH-NB 2 x 2/KTC and SLH-NB 3 x 2/KTC
 - Approved for the passive storage of flammable media
 - The legally required air exchange of at least 0.4 fold is achieved by venting slots situated directly above the sump tray and in the upper part of back wall and door.
 - Incl. ground connection in order to avoid dangerous electrostatic charge



Accessories please see pages 172/173!



SLH 3 x 2 KTC, galvanized, Article no. H61-2143-B



for water-endangering liquids



for flammable liquids (passive storage)

Approved	for water-endangering liquids		for flammable liquids (passive storage)	
Model	SLH 2 x 2/KTC	SLH 3 x 2/KTC	SLH-NB 2 x 2/KTC	SLH-NB 3 x 2/KTC
External dimensions W x D x H (mm)	2075 x 2075 x 2480	3075 x 2075 x 2385	2075 x 2075 x 2665	3075 x 2075 x 2565
Internal dimensions W x D x H (mm)	1980 x 1980 x 1970	2980 x 1980 x 1970	1980 x 1980 x 2150	2980 x 1980 x 2150
Door width (mm)	1950	2650	1950	2650
Sump capacity (l)	1000	1000	1000	1000
Capacity	1 KTC/IBC	2 KTC/IBC	1 KTC/IBC	2 KTC/IBC
Article no., galvanized	H61-2116-B	H61-2143-B	H63-1116-A	H63-1112-A
Article no., galvanized and exterior painted	H61-6116-B	H61-6143-B	H63-2116-A	H63-2112-A