

FASSROLLI

- ◆ Geeignet für Stahl- oder Kunststofffässer bis 200 Liter Inhalt
- ◆ Konstruktion aus Stahlblech verzinkt
- ◆ Traglast 250 kg
- ◆ Ø 610 mm, mit 4 Stück Polyamid-Lenkrollen Ø 80 mm
- ◆ FAR-1: geschlossene Ausführung mit dicht geschweißtem Boden, Randhöhe 110 mm
- ◆ FAR-1B: wie FAR-1 mit zusätzlichem Schiebebügel und Haltegurt, Schiebebügel pulverbeschichtet RAL 5012, lichtblau, anschraubbar
- ◆ FAR-2: offene Ausführung, Bauhöhe 140 mm, Ladehöhe 110 mm



FASSKARREN FÜR 200-LITER-STAHLFÄSSER

- ◆ Geeignet für Stahlfässer bis 200 Liter Inhalt
- ◆ Stabile Konstruktion aus Stahlrohr, pulverbeschichtet RAL 5012, lichtblau
- ◆ Mit verstellbarem Fassgreifer
- ◆ Radnaben mit Rollenlager
- ◆ Griff bei Anlieferung demontiert, einfache Montage
- ◆ Ausführung mit Stützrad Ø 200 mm, Lenkrolle, Vollgummibereifung



Typenbezeichnung	FK 1029-1	FK 1029-2	FK 1029-4
Räder	Vollgummi	Vollgummi	Luftbereifung
Ausstattung	ohne Stützrad	mit Stützrad	mit Stützrad
Rad ø in mm	250	250	260
Maße B x H in mm	740 x 1570	740 x 830	740 x 830
Artikel-Nr.	B69-6353-A	B69-6354-A	B69-6355-A

FASSKARRE FÜR 200-LITER-STAHL- UND KUNSTSTOFF-FÄSSER

- ◆ Geeignet für Kunststoff- und Stahlfässer bis 200 Liter Inhalt
- ◆ Stabile Konstruktion aus Stahlrohr lackiert RAL 5002 mit Abfüllstützrahmen
- ◆ Tragfähigkeit 400 kg
- ◆ Typ FK 1026-1 mit Luftbereifung, Räder ø 400 mm
- ◆ Typ FK 1026-1V mit Vollgummibereifung, Räder ø 400 mm
- ◆ Lieferung inkl. Zurrurt
- ◆ Absetzen der Fässer auf Lagerpaletten oder Auffangwannen bis 350 mm Höhe möglich

Ohne Abb.:
FK 1026-1V mit Vollgummibereifung,
Artikel-Nr. B69-6307-A



FASSKIPPWAGEN FÜR 200-LITER-FÄSSER

Die Fasskippwagen erleichtern in einfacher und sicherer Art das Einlagern von Fässern und das Abfüllen von Gefahrstoffen.

Funktion:

Die Fässer werden stehend aufgenommen, durch die Rohr-Hebelstange arretiert und über die Abrollkufen in Fahr- bzw. Abfüllstellung gebracht.

- ◆ Geeignet für Fässer bis 200 Liter Inhalt
- ◆ Stabile Konstruktion aus Stahlrohr lackiert RAL 5002
- ◆ Tragfähigkeit 250 kg
- ◆ Ausführung ST für 200-Liter-Stahlfässer mit PVC-Fassrollen
- ◆ Ausführung K für dünnwandige 200-Liter-Stahlfässer geeignet durch Ausstattung mit Metall-Tragrollen
- ◆ Für die Typen FKW 200 Kunststoff-Tropfwanne als Zubehör erhältlich, die Typen FKW-AW 200 standardmäßig mit großer Stahl-Auffangwanne
- ◆ Alle Typen standardmäßig komplett mit Hebelstange mit PVC-Griff



**FKW 200 ST (Abb. links) , Artikel-Nr. B69-6308-A, mit optionaler Kunststoff-Tropfwanne;
FKW 200 K (Abb. rechts) , Artikel-Nr. B69-6309-A, mit optionaler Kunststoff-Tropfwanne**



**FKW-AW 200 K,
Artikel-Nr. B69-6311-A**



**FKW-AW 200 ST,
Artikel-Nr. B69-6310-A**



Typenbezeichnung	FKW 200 ST	FKW 200 K	FKW-AW 200 ST	FKW-AW 200 K
Maße L x B x H in mm	830 x 500 x 550	830 x 500 x 550	1500 x 650 x 600	1500 x 650 x 600
Radsatz	2 x PVC-Lenkräder 2 x PVC-Festräder	2 x PVC-Lenkräder 2 x PVC-Festräder	2 x Vollgummiräder 2 x Standfüße	2 x Vollgummiräder 2 x Standfüße
Stahl-Auffangwanne				
Auffangvolumen in Liter	-	-	203	229
Artikel-Nr.	B69-6308-A	B69-6309-A	B69-6310-A	B69-6311-A

Zubehör	Artikel-Nr.	Artikel-Nr.
Kunststoff-Tropfwanne	B69-6312-A	B69-6312-A

FASSKLAMMER FKL-40 H

- ◆ Für stehende Fassaufnahme von geschlossenen 200-Liter-Fässern
- ◆ Für 200-Liter-Rollreifen- oder Sickenfässer (Fass ø 560-600 mm)
- ◆ Manuelle Bedienung
- ◆ Traglast max. 400 kg

Ausführung:

- ◆ Mit Aufhängeöse für Lasthaken, Greiferarme mit Haltepratzen, Handgriff



**FKL-40 H, RAL 5002,
Artikel-Nr. B69-6313-A**



**FKL-40 H, feuerverzinkt,
Artikel-Nr. B69-6330-A**

FASS-ZANGENGREIFER FZ-36 H

- ◆ Für liegende Fassaufnahme von 200-Liter-Stahlfässern
- ◆ Für 200-Liter-Rollreifen- oder Sickenfässer
- ◆ Aufnahme-Länge 760-910 mm
- ◆ Manuelle Bedienung
- ◆ Traglast max. 360 kg

Ausführung:

- ◆ Mit Aufhängeöse für Lasthaken, Arretiervorrichtung mit Handhebel



**FZ-36 H, RAL 5002,
Artikel-Nr. B69-6314-A**



**FZ-36 H, feuerverzinkt,
Artikel-Nr. B69-6331-A**

FASS-SPANNKLAUEN-RANDGREIFER FSP-R-50 H

- ◆ Für stehende oder liegende Fassaufnahme von 200-Liter-Stahlfässern
- ◆ Für 200-Liter-Rollreifen- oder Sickenfässer (Fass ø 560-600 mm)
- ◆ Manuelle Bedienung
- ◆ Traglast max. 500 kg

Ausführung:

- ◆ Mit Sicherheits-Arretierklau, Schäkel für Lasthaken



**FSP-R-50 H, RAL 5002,
Artikel-Nr. B69-6315-A**

FASS-BANDAGENGREIFER BG-600 H

- ◆ Für stehende Fassaufnahme von 200-Liter-Stahlfässern
- ◆ Für 200-Liter-Rollreifen- oder Sickenfässer (Fass ø 560-600 mm)
- ◆ Manuelle Bedienung
- ◆ Traglast max. 600 kg

Ausführung:

- ◆ Mit Kniehebelverschluss, verstellbare Feinregulierung, Kettengehänge und Aufhängeöse



**BG-600 H, RAL 5002,
Artikel-Nr. B69-6316-A**

FASSGREIFER 2216/1

- ◆ Für stehende Fassaufnahme von einem 200-Liter-Rollreifen- oder Sickenfass
- ◆ Auf den Gabelzinken zu arretierender Stapler-Aufsatz mit Verriegelungsautomatik
- ◆ An das Fass heranfahren, unterhalb der Sickenrinne positionieren und anpressen. Durch Druck öffnet sich die Greiferzange und umschließt das Fass.
- ◆ Inklusive Kette zur Sicherung vor ungewolltem Abrutschen



**FG 2216/1, RAL 2004 - reinorange, Artikel-Nr. B69-6356-A,
L x B x H in mm: 1285 x 710 x 150, Tragkraft: 400 kg**



FASSGREIFER 2215

- ◆ Stapleraufsatz für stehende Fassaufnahme von einem 200-Liter-Metall- oder Kunststoff-L-Ring-Fass
- ◆ Der höhenverstellbare Greifer setzt von oben am Rand des stehenden Fasses an und öffnet selbsttätig beim Absetzen.
- ◆ Inklusive Haltebacken mit Gummibeschichtung und Kette zur Sicherung vor ungewolltem Abrutschen



**FG 2215/1, RAL 2004 - reinorange,
Artikel-Nr. B69-6357-A,
L x B x H in mm: 1150 x 600 x 1000,
Tragkraft: 400 kg**



FASSKIPPER 2234/1

- ◆ Stapleraufsatz für stehende Fassaufnahme von einem 200-Liter-Rollreifen- oder Sickenfass
- ◆ Zum Transportieren, Kippen und Drehen
- ◆ Das Fass wird von Stahlriemen mit Exzenterverschluss gehalten. Der Kippvorgang wird über Handkurbel betätigt, inkl. Abrutschsicherung



**FK 2234/1, RAL 2004 - reinorange,
Artikel-Nr. B69-6358-A,
L x B x H in mm: 1270 x 1090 x 550,
Tragkraft: 360 kg**



DRUM HANDLING

DRUM ROLLER

- ◆ Suitable for steel or plastic drums with a capacity of up to 200 liter
- ◆ Galvanised sheet steel construction
- ◆ Load capacity 250 kg
- ◆ Ø 610 mm, with 4 polyamide swivel castors Ø 80 mm
- ◆ FAR-1: closed design with tightly welded base, rim height 110 mm
- ◆ FAR-1B: same as FAR-1 with additional push bar and safety strap, push bar powder-coated in RAL 5012, light blue, screw-on
- ◆ FAR-2: open design, height 140 mm, loading height 110 mm



DRUM TROLLEYS FOR 200-LITER STEEL DRUMS

- ◆ Suitable for steel drums with a capacity of up to 200 liter
- ◆ Robust construction made of steel tubing, powder-coated in RAL 5012, light blue
- ◆ With adjustable drum gripper
- ◆ Wheel hubs with roller bearings
- ◆ Handle dismantled on delivery, easy to assemble
- ◆ Version with support wheel Ø 200 mm, swivel castor, solid rubber tyres



Model	FK 1029-1	FK 1029-2	FK 1029-4
Wheels	solid rubber	solid rubber	pneumatic tyres
Facilities	without stabiliser wheel	with stabiliser wheel	with stabiliser wheel
Wheel ø (mm)	250	250	260
Dimensions W x H (mm)	740 x 1570	740 x 830	740 x 830
Article no.	B69-6353-A	B69-6354-A	B69-6355-A

DRUM TROLLEY FOR 200-LITER STEEL AND PLASTIC DRUMS

- ◆ Suitable for plastic and steel drums with a capacity of up to 200 liter
- ◆ Robust construction made of steel tubing painted in RAL 5002 with filling support frame
- ◆ Load capacity 400 kg
- ◆ Type FK 1026-1 with pneumatic tyres, wheels ø 400 mm
- ◆ Type FK 1026-1V with solid rubber tyres, wheels ø 400 mm
- ◆ Delivery includes lashing strap
- ◆ Drums can be placed on storage pallets or drip pans up to 350 mm high

Without illustration:
FK 1026-1V with solid rubber tyres,
Article no. B69-6307-A



DRUM TIPPING TROLLEY FOR 200-LITER DRUMS

The drum tipping trolleys facilitate the storage of drums and the filling of hazardous substances in a simple and safe manner.

Function:

The drum is picked up in an upright position, locked in place by the pipe lever bar and moved into the transport or filling position via the roll-off skids.

- ◆ Suitable for drums with a capacity of up to 200 liter
- ◆ Robust construction made of steel tubing, painted in RAL 5002
- ◆ Load capacity 250 kg
- ◆ Version ST for 200-liter steel drums with PVC drum rollers
- ◆ Version K for thin-walled 200-liter steel drums thanks to metal support rollers
- ◆ Plastic drip tray available as an accessory for FKW 200 models; FKW-AW 200 models come with a large steel drip tray as standard.
- ◆ All types come complete with lever bar with PVC handle as standard



FKW 200 ST (Fig. left), Article no. B69-6308-A, with optional plastic drip tray;
FKW 200 K (Fig. right), Article no. B69-6309-A, with optional plastic drip tray



FKW-AW 200 K,
Article no. B69-6311-A



FKW-AW 200 ST,
Article no. B69-6310-A



Model	FKW 200 ST	FKW 200 K	FKW-AW 200 ST	FKW-AW 200 K
Dimensions L x W x H in mm	830 x 500 x 550	830 x 500 x 550	1500 x 650 x 600	1500 x 650 x 600
Wheel set	2 x PVC steering wheels 2 x PVC fixed wheels	2 x PVC steering wheels 2 x PVC fixed wheels	2 x solid rubber wheels 2 x base plates	2 x solid rubber wheels 2 x base plates
Steel drip tray				
Sump capacity (l)	-	-	203	229
Article no.	B69-6308-A	B69-6309-A	B69-6310-A	B69-6311-A

Accessories	Article no.	Article no.
Plastic drip tray	B69-6312-A	B69-6312-A

DRUM HANDLING

DRUM CLAMP FKL-40 H

- ◆ For upright storage of closed 200-liter drums
- ◆ For 200-liter roll-on drums or ribbed drums (drum ø 560–600 mm)
- ◆ Manual operation
- ◆ Maximum load capacity 400 kg

Execution:

- ◆ With suspension eye for load hook, gripper arms with retaining claws, handle



**FKL-40 H, RAL 5002,
Article no. B69-6313-A**



**FKL-40 H, fire-galvanized,
Article no. B69-6330-A**

DRUM CLAMP GRIPPER FZ-36 H

- ◆ For horizontal handling of 200-liter steel drums
- ◆ For 200-liter roll-on drums or ribbed drums
- ◆ Mounting length 760–910 mm
- ◆ Manual operation
- ◆ Maximum load capacity 360 kg

Execution:

- ◆ With suspension eye for load hook, locking device with hand lever



**FZ-36 H, RAL 5002,
Article no. B69-6314-A**



**FZ-36 H, fire-galvanized,
Article no. B69-6331-A**

DRUM CLAMP EDGE GRIPPER FSP-R-50 H

- ◆ For upright or horizontal storage of 200-liter steel drums
- ◆ For 200-liter roll-on drums or ribbed drums (drum ø 560–600 mm)
- ◆ Manual operation
- ◆ Maximum load capacity 500 kg

Execution:

- ◆ With safety locking claw, shackle for load hook



**FSP-R-50 H, RAL 5002,
Article no. B69-6315-A**

DRUM BANDAGE GRIPPER BG-600 H

- ◆ For upright storage of 200-liter steel drums
- ◆ For 200-liter roll-on drums or ribbed drums (drum ø 560–600 mm)
- ◆ Manual operation
- ◆ Maximum load capacity 600 kg

Execution:

- ◆ With toggle clamp, adjustable fine adjustment, chain sling and suspension eye



**BG-600 H, RAL 5002,
Article no. B69-6316-A**

DRUM GRIPPER 2216/1

- ◆ For upright storage of 200-liter roll-on drum or ribbed drum
- ◆ Forklift attachment with automatic locking mechanism to be locked onto the fork prongs
- ◆ Drive up to the drum, position it below the bead groove and press down. The pressure causes the gripper tongs to open and enclose the drum.
- ◆ Includes chain to prevent accidental slipping



**FG 2216/1, RAL 2004 - pure orange, Article no. B69-6356-A,
L x W x H (mm): 1285 x 710 x 150, Load capacity: 400 kg**



DRUM GRIPPER 2215

- ◆ Forklift attachment for upright drum handling of a 200-liter metal or plastic L-ring drum
- ◆ The height-adjustable gripper attaches to the top edge of the upright drum and opens automatically when lowered.
- ◆ Includes retaining jaws with rubber coating and chain to prevent unwanted slipping



FG 2215/1, RAL 2004 - pure orange,
Article no. B69-6357-A,
L x W x H (mm): 1150 x 600 x 1000,
Load capacity: 400 kg



DRUM TIPPER 2234/1

- ◆ Forklift attachment for upright drum handling of a 200-liter roll-type or ribbed drum
- ◆ For transporting, tipping and turning
- ◆ The barrel is held in place by steel straps with an eccentric lock. The tilting process is operated by a hand crank, including slip protection.



FK 2234/1, RAL 2004 - pure orange,
Article no. B69-6358-A,
L x W x H (mm): 1270 x 1090 x 550,
Load capacity: 360 kg

