




LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER - CLASSIC BEGEHBAR

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ **Geeignet zur Innen- und Außenaufstellung**
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Türen selbstschließend
- ◆ Kranösen serienmäßig (nur für Leertransport)
- ◆ Lackierung RAL 7035 - lichtgrau
- ◆ Umfangreiches Zubehör



BRANDVERHALTEN

- Im Brandfall werden die Tür, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststallanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen



WSC 2-CL/F90,
Artikel-Nr. C64-4009-B,
zur Lagerung von Kleingebinden



WSC 5-CL/F90, Artikel-Nr. C64-4014-B,
zur Lagerung von Kleingebinden und Fässern,
mit optionalem Gitterrost-Kleingebinderegal



Brandschutzcontainer
aus Beton finden
Sie ab Seite 214!

Typenbezeichnung	WSC 2-CL/F90	WSC 3-CL/F90	WSC 4-CL/F90	WSC 5-CL/F90	WSC 6-CL/F90	WSC 7-CL/F90	WSC 8-CL/F90
Außenmaße B x T x H in mm	2170 x 2500 x 2440	3000 x 2500 x 2440	4000 x 2500 x 2440	5000 x 2500 x 2440	6000 x 2500 x 2440	7000 x 2500 x 2440	8000 x 2500 x 2440
Innenmaße B x T x H in mm	1930 x 2100 x 2120	2750 x 2100 x 2120	3750 x 2100 x 2120	4750 x 2100 x 2120	5750 x 2100 x 2120	6750 x 2100 x 2120	7750 x 2100 x 2120
Auffangvolumen in Liter	600	800	1200	1400	1800	2 x 1100	2 x 1200
Belastung in kg/m²	1000	1000	1000	1000	1000	1000	1000
Artikel-Nr. Tür B x H 1250 x 2000 mm (EF)*	C64-4008-B	C64-4010-B	C64-4012-B	C64-4014-B	C64-4016-B	C64-4018-B	C64-4020-B
Artikel-Nr. Tür B x H 1750 x 2000 mm (DF)**	C64-4009-B	C64-4011-B	C64-4013-B	C64-4015-B	C64-4017-B	C64-4019-B	C64-4021-B

* EF = einflügelige Tür

** DF = doppelflügelige Tür

Zubehör	Artikel-Nr.
Ex-geschützte Technische Zwangsentlüftung	C64-3100-A
LED-Leuchte Ex-Zone II, 230 V, 40 W, Leuchtenlichtstrom 6320 Lumen	C64-3125-A
LED-Leuchte Ex-Zone I, 230 V, 40 W, Leuchtenlichtstrom 6320 Lumen	C64-3124-A
Ex-geschützte Heizung 2 kW	C64-3103-A
Ex-geschützte Heizung 3 kW	C64-3104-A
Feststellanlage für einflügelige Tür	C64-3106-A
Feststellanlage für doppelflügelige Tür	C64-3107-A
Ex-geschützte Abluftüberwachung mit Signalhupe	C64-3109-A
Schaltkasten	C64-3114-A

Zubehör	Artikel-Nr.
Kleingebinderegal Grundfeld mit 4 Gitterrost-Lagerebenen, B x T x H in mm = 1060 x 600 x 2000	C64-2080-A
Kleingebinderegal Anbaufeld mit 4 Gitterrost-Lagerebenen, B x T x H in mm = 1010 x 600 x 2000	C64-2081-A
Kleingebinderegal Grundfeld mit 4 Gitterrost-Lagerebenen, B x T x H in mm = 1360 x 600 x 2000	C64-2085-A
Kleingebinderegal Anbaufeld mit 4 Gitterrost-Lagerebenen, B x T x H in mm = 1310 x 600 x 2000	C64-2086-A
Auffahrrampe für Fasskarre B x L in mm = 1000 x 800	C64-3150-A
Auffahrrampe für Gabelhubwagen B x L in mm = 1000 x 1200	C64-3151-A



LACONT FIRE PROTECTION CONTAINER - WALK-IN CLASSIC

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sump as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Lifting attachments for cranes (for empty transport only) as standard
- ◆ Outer body painted in RAL 7035 - light grey
- ◆ Wide range of accessories



FIRE BEHAVIOR

- If fire occurs the door, door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process



**WSC 2-CL/F90,
Article no. C64-4009-B,
for storing small containers**



**WSC 5-CL/F90, Article no. C64-4014-B,
for storing small containers and drums,
with optional grid shelving**



Concrete fire protection containers can be found on page 214!

Model	WSC 2-CL/F90	WSC 3-CL/F90	WSC 4-CL/F90	WSC 5-CL/F90	WSC 6-CL/F90	WSC 7-CL/F90	WSC 8-CL/F90
External dimensions W x D x H (mm)	2170 x 2500 x 2440	3000 x 2500 x 2440	4000 x 2500 x 2440	5000 x 2500 x 2440	6000 x 2500 x 2440	7000 x 2500 x 2440	8000 x 2500 x 2440
Internal dimensions W x D x H (mm)	1930 x 2100 x 2120	2750 x 2100 x 2120	3750 x 2100 x 2120	4750 x 2100 x 2120	5750 x 2100 x 2120	6750 x 2100 x 2120	7750 x 2100 x 2120
Sump capacity (l)	600	800	1200	1400	1800	2 x 1100	2 x 1200
Max. load (kg/m ²)	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	C64-4008-B	C64-4010-B	C64-4012-B	C64-4014-B	C64-4016-B	C64-4018-B	C64-4020-B
Article no. door W x H (mm) 1750 x 2000 (DD)**	C64-4009-B	C64-4011-B	C64-4013-B	C64-4015-B	C64-4017-B	C64-4019-B	C64-4021-B

* SD = single door

** DD = double door

Accessories	Article no.
Ex-proof forced ventilation	C64-3100-A
LED Lamp ex-zone II, 230 V, 40 W, effective luminous flux 6320 lm	C64-3125-A
LED Lamp ex-zone I, 230 V, 40 W, effective luminous flux 6320 lm	C64-3124-A
Ex-proof heating 2 kW	C64-3103-A
Ex-proof heating 3 kW	C64-3104-A
Door hold-open device for single door	C64-3106-A
Door hold-open device for double door	C64-3107-A
Ex-proof exhaust air monitoring with signal horn	C64-3109-A
Switch box	C64-3114-A

Accessories	Article no.
Shelf for small containers, basic unit with 4 grid-type storage levels, W x D x H (mm) = 1060 x 600 x 2000	C64-2080-A
Shelf for small containers, extension unit with 4 grid-type storage levels, W x D x H (mm) = 1010 x 600 x 2000	C64-2081-A
Shelf for small containers, basic unit with 4 grid-type storage levels, W x D x H (mm) = 1360 x 600 x 2000	C64-2085-A
Shelf for small containers, extension unit with 4 grid-type storage levels, W x D x H (mm) = 1310 x 600 x 2000	C64-2086-A
Drive-on ramp W x L (mm) = 1000 x 800 for drum carts	C64-3150-A
Drive-on ramp W x L (mm) = 1000 x 1200 for pallet truck	C64-3151-A