



LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER - COMFORT BEGEHBAR

Ausführung:

Technische Ausstattung wie WSC - CLASSIC Seite 207, jedoch mit einer lichten

Innenhöhe von 2520 mm und nutzbarer **Lagertiefe von 2100 mm**.

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ **Geeignet zur Innen- und Außenaufstellung**
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Türen selbstschließend
- ◆ Kranösen serienmäßig (nur für Leertransport)



Ex-geschützte Heizung



WSC 4-CO/F90,
Artikel-Nr. C64-4040-B,
mit einflügeliger Tür und
optionaler Auffahrrampe



Ausrüstung mit Regalteilen zur Nutzung als Kleingebindelager



Zubehörteile, wie Technische Belüftung, Heizung, Beleuchtung und Regale finden Sie auf Seite 207!

Typenbezeichnung	WSC 2-CO/F90	WSC 3-CO/F90	WSC 4-CO/F90	WSC 5-CO/F90	WSC 6-CO/F90	WSC 7-CO/F90	WSC 8-CO/F90
Außenmaße B x T x H in mm	2170 x 2500 x 2840	3000 x 2500 x 2840	4000 x 2500 x 2840	5000 x 2500 x 2840	6000 x 2500 x 2840	7000 x 2500 x 2840	8000 x 2500 x 2840
Innenmaße B x T x H in mm	1930 x 2100 x 2520	2750 x 2100 x 2520	3750 x 2100 x 2520	4750 x 2100 x 2520	5750 x 2100 x 2520	6750 x 2100 x 2520	7750 x 2100 x 2520
Auffangvolumen in Liter	600	800	1200	1400	1800	2 x 1100	2 x 1200
Belastung in kg/m²	1000	1000	1000	1000	1000	1000	1000
Artikel-Nr. Tür B x H 1250 x 2000 mm (EF)*	C64-4036-B	C64-4038-B	C64-4040-B	C64-4042-B	C64-4044-B	C64-4046-B	C64-4048-B
Artikel-Nr. Tür B x H 1750 x 2000 mm (DF)**	C64-4037-B	C64-4039-B	C64-4041-B	C64-4043-B	C64-4045-B	C64-4047-B	C64-4049-B

* EF = einflügelige Tür

** DF = doppelflügelige Tür



FIRE PROTECTION CONTAINER F90 STEEL




LACONT FIRE PROTECTION CONTAINER - WALK-IN COMFORT

Execution:

Technically as WSC Classic on page 207, but **internal height 2520 mm** and usable **storage depth 2100 mm**.

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Lifting attachments for cranes (for empty transport only) as standard



Ex-proof heating



WSC 4-CO/F90,
Article no. C64-4040-B,
with single door and
optional drive-on ramp



Equipped with shelving for use as small container store



Accessories such as forced ventilation, heating, illumination and shelving can be found on page 207!

Model	WSC 2-CO/F90	WSC 3-CO/F90	WSC 4-CO/F90	WSC 5-CO/F90	WSC 6-CO/F90	WSC 7-CO/F90	WSC 8-CO/F90
External dimensions W x D x H (mm)	2170 x 2500 x 2840	3000 x 2500 x 2840	4000 x 2500 x 2840	5000 x 2500 x 2840	6000 x 2500 x 2840	7000 x 2500 x 2840	8000 x 2500 x 2840
Internal dimensions W x D x H (mm)	1930 x 2100 x 2520	2750 x 2100 x 2520	3750 x 2100 x 2520	4750 x 2100 x 2520	5750 x 2100 x 2520	6750 x 2100 x 2520	7750 x 2100 x 2520
Sump capacity (l)	600	800	1200	1400	1800	2 x 1100	2 x 1200
Max. load (kg/m ²)	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	C64-4036-B	C64-4038-B	C64-4040-B	C64-4042-B	C64-4044-B	C64-4046-B	C64-4048-B
Article no. door W x H (mm) 1750 x 2000 (DD)**	C64-4037-B	C64-4039-B	C64-4041-B	C64-4043-B	C64-4045-B	C64-4047-B	C64-4049-B

* SD = single door

** DD = double door