




LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR FASSLAGERUNG

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ Zur Fasslagerung mit einflügeliger Tür zur Innen- und Außenaufstellung geeignet
- ◆ Stahlauffangwanne nach AwsV komplett mit Gitterrostabdeckung
- ◆ Tür selbstschließend
- ◆ Lackierung RAL 7035 - lichtgrau
- ◆ Umfangreiches Zubehör



WSC-Fass 4/F90,
Artikel-Nr. C64-4002-B



BRANDVERHALTEN

- Im Brandfall werden die Tür, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststellanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen



- Ex-geschützte Abluftüberwachung mit Signalhupe
- Türhalteanlage



K-90 Absperrvorrichtung



Optionale Außenbeleuchtung

Typenbezeichnung	WSC-Fass 2/F90	WSC-Fass 4/F90
Außenmaße B x T x H in mm	1720 x 1540 x 2325	1720 x 1840 x 2325
Innenmaße B x T x H in mm	1360 x 950 x 1900	1360 x 1250 x 1900
Auffangvolumen in Liter	220	220
Kapazität à 200-Liter-Fässer	2 auf Europalette	4 auf Chemiepalette
Artikel-Nr.,		
Tür B x H in mm = 1350 x 2000 (EF)	C64-4001-B	C64-4002-B

Zubehör	Artikel- Nr.
Ex-geschützte technische Zwangsventilation	C64-3116-A
LED-Leuchte Ex-Zone II, 230 V, 15 W, Leuchtenlichtstrom 2170 Lumen	H61-9131-A
Ex-geschützte Heizung 2 kW	C64-3103-A
Feststellanlage für einflügelige Tür	C64-3106-A
Schaltkasten	C64-3114-A
Potentialausgleich	C64-3113-A
Ex-geschützte Abluftüberwachung mit Signalhupe	C64-3109-A
zusätzliche Schallgeber-Blitzleuchtenkombination	C64-3110-A



Ex-geschützter Abluftventilator
inkl. Abluftüberwachung

LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR KTC-LAGERUNG

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ Zur KTC-Lagerung mit ein- oder zweiflügeliger Tür zur Innen- und Außenaufstellung geeignet
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Tür/en selbstschließend
- ◆ Lackierung RAL 7035 - lichtgrau
- ◆ Umfangreiches Zubehör



WSC-KTC 2/F90,
Artikel-Nr. C64-4004-B



BRANDVERHALTEN

- Im Brandfall werden die Türen, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststellanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen

Typenbezeichnung	WSC-KTC 1/F90	WSC-KTC 2/F90
Außenmaße B x T x H* in mm	1730 x 1840 x 2665	3270 x 1770 x 2480
Innenmaße B x T x H in mm	1360 x 1260 x 1900	2900 x 1300 x 1900
Auffangvolumen in Liter	1000	1000
Kapazität à KTC	1	2
Artikel-Nr., Tür B x H in mm = 1350 x 2000 (EF)	C64-4003-B	-
Artikel-Nr., Tür B x H in mm = 2900 x 2000 (DF)	-	C64-4004-B

* Außenmaße zuzüglich Fußplatten

Zubehör	Artikel- Nr.
Ex-geschützte technische Zwangsentlüftung	C64-3116-A
LED-Leuchte Ex-Zone II, 230 V, 15 W, Leuchtenlichtstrom 2170 Lumen	H61-9131-A
Ex-geschützte Heizung 2 kW	C64-3103-A
Feststellanlage für einflügelige Tür	C64-3106-A
Feststellanlage für zweiflügelige Tür	C64-3107-A
Schaltkasten	C64-3114-A
Potentialausgleich	C64-3113-A
Ex-geschützte Abluftüberwachung mit Signalhupe	C64-3109-A
zusätzliche Schallgeber-Blitzleuchtenkombination	C64-3110-A



WSC-KTC 1/F90,
Artikel-Nr. C64-4003-B



LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR PALETTENLAGERUNG MIT FLÜGELTÜREN

Diese Typenreihe ist speziell zur Einlagerung von Euro- oder Chemiepaletten sowie KTC/IBC geeignet. Bei Ausführung mit einer Türfeststelleinrichtung können die Türen im Arbeitsprozess offen gehalten werden. Somit kann der Brandschutzcontainer problemlos von einer Person bedient werden.

Ausstattung:

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ **Geeignet zur Innen- und Außenaufstellung**
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Türen selbstschließend
- ◆ Lackierung RAL 5015 - himmelblau



WSC-T-E.2-30 DF/F90,
Artikel-Nr. C64-3001-A
in Sonderfarbe



Zur Realisierung der optimalen Lagerbedingung steht ein umfangreiches Zubehör zur Auswahl, wie technische Belüftung, Beleuchtung, Heizung, Kühlung, Türfeststellanlage, Brandmeldung!



WSC-T-E.2-54 DF/F90,
Artikel-Nr. C64-3004-A



BRANDVERHALTEN

- Im Brandfall werden die Türen, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststellanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen



Abluftkanal mit K-90 Absperrvorrichtung

Typenbezeichnung	WSC-T-E.2-27 DF/F90	WSC-T-E.2-30 DF/F90	WSC-T-E.2-54 DF/F90	WSC-T-E.2-60 DF/F90
Außenmaße B x T x H* in mm	3070 x 1800 x 3700	3370 x 1800 x 3280	6140 x 1800 x 3700	6740 x 1800 x 3280
Fachmaße B x T x H** in mm	2700 x 1300 x 1400	3000 x 1300 x 1250	2700 x 1300 x 1400	3000 x 1300 x 1250
Anzahl der Lagerebenen	2	2	2	2
Auffangvolumen in Liter	1000	650	2 x 1000	2 x 650
Belastung in kg/m²	1500	1000	1500	1000
Kapazität 200-Liter-Fässer auf Europalette / auf Chemiepalette	12 / 16	12 / 16	24 / 32	24 / 32
Kapazität 1000-Liter-KTC/IBC	4	-	8	-
Tür B x H in mm (Baurichtmaß)	2700 x 3000	3000 x 2700	2 x 2700 x 3000	2 x 3000 x 2700
Artikel-Nr.	C64-3000-A	C64-3001-A	C64-3004-A	C64-3005-A

* Außenmaße zuzüglich Fußplatten

** Fachmaße und angegebene Kapazität ohne Berücksichtigung von elektrischen Einbauten (Lüftung, Heizung, usw.)




LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR PALETTENLAGERUNG MIT SCHIEBETÜREN

Durch den Einsatz von Schiebetüren reduziert sich der Platzbedarf des Brandschutzlagers nur auf die Grundfläche des Containers. Zusätzliche und teure Lagerfläche wird nicht benötigt und kann anderweitig genutzt werden.

Ausstattung:

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ **Geeignet zur Innen- und Außenaufstellung**
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Türen im Brandfall selbstschließend
- ◆ Lackierung RAL 5015 - himmelblau



BRANDVERHALTEN

- Im Brandfall werden die Türen automatisch geschlossen
- Türen, Türritzen, Zu- und Abluftöffnung werden hermetisch abgeschlossen



WSC-T-E.2-70 ST/F90,
Artikel-Nr. C64-3012-A



Schaltschrank mit
zentraler Steuerung
und Bedienelementen



Mit Brandschutzgutachten



Zur Realisierung der optimalen Lagerbedingung steht ein umfangreiches Zubehör zur Auswahl, wie technische Belüftung, Beleuchtung, Heizung, Kühlung, Brandmeldung!



WSC-T-E.2-80 ST/F90,
Artikel-Nr. C64-3013-A, in Sonderfarbe

Typenbezeichnung	WSC-T-E.2-70 ST/F90	WSC-T-E.2-80 ST/F90
Außenmaße B x T x H* in mm	7740 x 1900 x 3700	8480 x 1900 x 3700
Fachmaße B x T x H** in mm	3380 x 1300 x 1465	3900 x 1300 x 1500
Anzahl der Lagerebenen	2	2
Auffangvolumen in Liter	2 x 1000	2 x 1000
Belastung in kg/m ²	1500	1500
Kapazität 200-Liter-Fässer auf Europalette / auf Chemiepalette	24 / 32	32 / 48
Kapazität 1000-Liter-KTC/IBC	12	12
Anzahl der Schiebetüren	2	2
Artikel-Nr.	C64-3012-A	C64-3013-A

* Außenmaße zuzüglich Fußplatten

** Fachmaße und angegebene Kapazität ohne Berücksichtigung von elektrischen Einbauten (Lüftung, Heizung, usw.)



FIRE PROTECTION CONTAINER F90 STEEL



Explanations see practical informations on page 9 and 90!

LACONT FIRE PROTECTION CONTAINER FOR DRUM STORAGE

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ For the storage of drums with one-winged door
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey
- ◆ Wide range of accessories



WSC-Fass 4/F90,
Article no. C64-4002-B



FIRE BEHAVIOR

- If fire occurs the door, door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process



- Ex-proof exhaust air monitoring with signal horn
- Door hold-open device



K-90 shut-off device



Optional external lighting

Model	WSC-Fass 2/F90	WSC-Fass 4/F90
External dimensions W x D x H (mm)	1720 x 1540 x 2325	1720 x 1840 x 2325
Internal dimensions W x D x H (mm)	1360 x 950 x 1900	1360 x 1250 x 1900
Sump capacity (l)	220	220
Capacity, 200 liter drum	2 on Euro pallet	4 on chemical pallet
Article no., door W x H (mm) = 1350 x 2000 (SD)	C64-4001-B	C64-4002-B

Accessories	Article no.
Ex-proof forced ventilation	C64-3116-A
LED Lamp ex-zone II, 230 V, 15 W, effective luminous flux 2170 lm	H61-9131-A
Ex-proof heating 2 kW	C64-3103-A
Door hold-open device for single door	C64-3106-A
Switch box	C64-3114-A
Potential equalizing bar	C64-3113-A
Ex-proof exhaust air monitoring with signal horn	C64-3109-A
Combination of flashing light and sound generator	C64-3110-A



Ex-proof exhaust fan
incl. exhaust air monitoring



LACONT FIRE PROTECTION CONTAINER FOR KTC/IBC STORAGE

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ For the storage of KTC with one- or two-winged door(s),
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey
- ◆ Wide range of accessories



WSC-KTC 2/F90,
Article no. C64-4004-B



FIRE BEHAVIOR

- If fire occurs the door(s), door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process

Model	WSC-KTC 1/F90	WSC-KTC 2/F90
External dimensions W x D x H* (mm)	1730 x 1840 x 2665	3270 x 1770 x 2480
Internal dimensions W x D x H (mm)	1360 x 1260 x 1900	2900 x 1300 x 1900
Sump capacity (l)	1000	1000
Capacity, KTC/IBC	1	2
Article no., door W x H (mm) = 1350 x 2000 (SD)	C64-4003-B	-
Article no., door W x H (mm) = 2900 x 2000 (DD)	-	C64-4004-B

* External dimensions plus base plates

Accessories	Article no.
Ex-proof forced ventilation	C64-3116-A
LED Lamp ex-zone II, 230 V, 15 W, effective luminous flux 2170 lm	H61-9131-A
Ex-proof heating, 2 kW	C64-3103-A
Door hold-open device for single door	C64-3106-A
Door hold-open device for double door	C64-3107-A
Switch box	C64-3114-A
Potential equalizing bar	C64-3113-A
Ex-proof exhaust air monitoring with signal horn	C64-3109-A
Combination of flashing light and sound generator	C64-3110-A



WSC-KTC 1/F90,
Article no. C64-4003-B



LACONT FIRE PROTECTION CONTAINER FOR PALLET STORAGE WITH DOUBLE DOORS

This series is particularly suitable for storing goods on euro- or chemical pallets or KTC/IBC. The Thermolock system allows the doors to be left open during the work process. Therefore the BSC can be used by one person without any problems.

Execution:

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey or RAL 5015 - sky blue



In order to realize the optimum storage conditions a wide range of accessories is available such as technical forced ventilation, lighting, heating, cooling system, door hold-open device, fire warning device!



WSC-T-E.2-30 DF/F90,
Article no. C64-3001-A



WSC-T-E.2-54 DF/F90,
Article no. C64-3004-A



FIRE BEHAVIOR

- If fire occurs the doors, door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process



Air exhaust duct with K-90 shut-off device

Model	WSC-T-E.2-27 DF/F90	WSC-T-E.2-30 DF/F90	WSC-T-E.2-54 DF/F90	WSC-T-E.2-60 DF/F90
External dimensions W x D x H* (mm)	3070 x 1800 x 3700	3370 x 1800 x 3280	6140 x 1800 x 3700	6740 x 1800 x 3280
Compartment dimensions W x D x H** (mm)	2700 x 1300 x 1400	3000 x 1300 x 1250	2700 x 1300 x 1400	3000 x 1300 x 1250
Number of storage levels	2	2	2	2
Sump capacity (l)	1000	650	2 x 1000	2 x 650
Max. load (kg/m²)	1500	1000	1500	1000
Capacity, 200 liter drums on euro- / chemical pallets	12 / 16	12 / 16	24 / 32	24 / 32
Capacity, KTCs/IBCs	4	-	8	-
Door W x H (mm) (basic dimensions)	2700 x 3000	3000 x 2700	2 x 2700 x 3000	2 x 3000 x 2700
Article no.	C64-3000-A	C64-3001-A	C64-3004-A	C64-3005-A

* External dimensions plus base plates

** Compartment dimensions and stated capacities without considering electrical installations (ventilation, heating, etc.)



LACONT FIRE PROTECTION CONTAINER FOR PALLET STORAGE WITH SLIDING DOORS

The use of sliding doors reduces the space requirement of the fire protection store to the base area of the container only. Additional and expensive storage space is not required and can be used for other purposes.

Execution:

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey or RAL 5015 - sky blue



FIRE BEHAVIOR

- If a fire occurs the doors close automatically
- Doors, door gaps, air in- and outlet slots are sealed hermetically



WSC-T-E.2-70 ST/F90,
Article no. C64-3012-A



Control cabinet with
central control and
operating elements



With a fire
protection certificate



In order to realize the optimum storage conditions a wide range of accessories is available such as technical forced ventilation, lighting, heating, cooling system, door hold-open device, fire warning device!



WSC-T-E.2-80 ST/F90,
Article no. C64-3013-A, in special color

Model	WSC-T-E.2-70 ST/F90	WSC-T-E.2-80 ST/F90
External dimensions W x D x H* (mm)	7740 x 1900 x 3700	8480 x 1900 x 3700
Compartment dimensions W x D x H** (mm)	3380 x 1300 x 1465	3900 x 1300 x 1500
Number of storage levels	2	2
Sump capacity (l)	2 x 1000	2 x 1000
Max. load (kg/m²)	1500	1500
Capacity, 200 liter drums on euro- / chemical pallets	24 / 32	32 / 48
Capacity, 1000 liter KTCs/IBCs	12	12
Number of sliding doors	2	2
Article no.	C64-3012-A	C64-3013-A

* External dimensions plus base plates

** Compartment dimensions and stated capacities without considering electrical installations (ventilation, heating, etc.)