



LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER - PREMIUM BEGEHBAR

Ausführung:

Technische Ausstattung wie WSC - CLASSIC Seite 207, jedoch mit einer lichten **Innenhöhe von 2120 mm** und nutzbarer **Lagertiefe von 2550 mm**.



**WSC 6-PR/F90,
Artikel-Nr. C64-4031-B,
mit doppelflügeliger Tür**

Typenbezeichnung	WSC 2-PR/F90	WSC 3-PR/F90	WSC 4-PR/F90	WSC 5-PR/F90	WSC 6-PR/F90	WSC 7-PR/F90	WSC 8-PR/F90
Außenmaße B x T x H in mm	2170 x 2950 x 2440	3000 x 2950 x 2440	4000 x 2950 x 2440	5000 x 2950 x 2440	6000 x 2950 x 2440	7000 x 2950 x 2440	8000 x 2950 x 2440
Innenmaße B x T x H in mm	1930 x 2550 x 2120	2750 x 2550 x 2120	3750 x 2550 x 2120	4750 x 2550 x 2120	5750 x 2550 x 2120	6750 x 2550 x 2120	7750 x 2550 x 2120
Auffangvolumen in Liter	700	1000	1400	1800	2 x 1100	2 x 1300	2 x 1500
Belastung in kg/m ²	1000	1000	1000	1000	1000	1000	1000
Artikel-Nr. Tür B x H 1250 x 2000 mm (EF)*	C64-4022-B	C64-4024-B	C64-4026-B	C64-4028-B	C64-4030-B	C64-4032-B	C64-4034-B
Artikel-Nr. Tür B x H 1750 x 2000 mm (DF)**	C64-4023-B	C64-4025-B	C64-4027-B	C64-4029-B	C64-4031-B	C64-4033-B	C64-4035-B

* EF = einflügelige Tür ** DF = doppelflügelige Tür

LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER - SUPERIOR BEGEHBAR



**WSC 4-SU/F90,
Artikel-Nr. C64-4054-B,
mit einflügeliger Tür**



Ausführung:

Technische Ausstattung wie WSC - CLASSIC Seite 207, jedoch mit dem größten Lagervolumen der WSC, einer lichten **Innenhöhe von 2520 mm** und nutzbarer **Lagertiefe von 2550 mm**.



Zubehörteile, wie Technische Belüftung, Heizung, Beleuchtung und Regale finden Sie auf Seite 207!


Typenbezeichnung	WSC 2-SU/F90	WSC 3-SU/F90	WSC 4-SU/F90	WSC 5-SU/F90	WSC 6-SU/F90	WSC 7-SU/F90	WSC 8-SU/F90
Außenmaße B x T x H in mm	2170 x 2950 x 2840	3000 x 2950 x 2840	4000 x 2950 x 2840	5000 x 2950 x 2840	6000 x 2950 x 2840	7000 x 2950 x 2840	8000 x 2950 x 2840
Innenmaße B x T x H in mm	1930 x 2550 x 2520	2750 x 2550 x 2520	3750 x 2550 x 2520	4750 x 2550 x 2520	5750 x 2550 x 2520	6750 x 2550 x 2520	7750 x 2550 x 2520
Auffangvolumen in Liter	700	1000	1400	1800	2 x 1100	2 x 1300	2 x 1500
Belastung in kg/m ²	1000	1000	1000	1000	1000	1000	1000
Artikel-Nr. Tür B x H 1250 x 2000 mm (EF)*	C64-4050-B	C64-4052-B	C64-4054-B	C64-4056-B	C64-4058-B	C64-4060-B	C64-4062-B
Artikel-Nr. Tür B x H 1750 x 2000 mm (DF)**	C64-4051-B	C64-4053-B	C64-4055-B	C64-4057-B	C64-4059-B	C64-4061-B	C64-4063-B

* EF = einflügelige Tür ** DF = doppelflügelige Tür

LACONT FIRE PROTECTION CONTAINER - WALK-IN PREMIUM

Execution:

Technically as WSC Classic on page 207, but
internal height 2120 mm and usable **storage depth 2550 mm**.



**WSC 6-PR/F90,
Article no. C64-4031-B,
with double door**

i Accessories such as forced ventilation, heating, illumination and shelving can be found on page 207!


Model	WSC 2-PR/F90	WSC 3-PR/F90	WSC 4-PR/F90	WSC 5-PR/F90	WSC 6-PR/F90	WSC 7-PR/F90	WSC 8-PR/F90
External dimensions W x D x H (mm)	2170 x 2950 x 2440	3000 x 2950 x 2440	4000 x 2950 x 2440	5000 x 2950 x 2440	6000 x 2950 x 2440	7000 x 2950 x 2440	8000 x 2950 x 2440
Internal dimensions W x D x H (mm)	1930 x 2550 x 2120	2750 x 2550 x 2120	3750 x 2550 x 2120	4750 x 2550 x 2120	5750 x 2550 x 2120	6750 x 2550 x 2120	7750 x 2550 x 2120
Sump capacity (l)	700	1000	1400	1800	2 x 1100	2 x 1300	2 x 1500
Max. load (kg/m ²)	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	C64-4022-B	C64-4024-B	C64-4026-B	C64-4028-B	C64-4030-B	C64-4032-B	C64-4034-B
Article no. door W x H (mm) 1750 x 2000 (DD)**	C64-4023-B	C64-4025-B	C64-4027-B	C64-4029-B	C64-4031-B	C64-4033-B	C64-4035-B

* SD = single door ** DD = double door

LACONT FIRE PROTECTION CONTAINER - WALK-IN SUPERIOR



**WSC 4-SU/F90,
Article no. C64-4054-B,
with single door**



Execution:

Technically as WSC Classic on page 207, but with the largest storage volume of all WSCs, **internal height 2520 mm** and usable **storage depth 2550 mm**.

i Accessories such as forced ventilation, heating, illumination and shelving can be found on page 207!

Model	WSC 2-SU/F90	WSC 3-SU/F90	WSC 4-SU/F90	WSC 5-SU/F90	WSC 6-SU/F90	WSC 7-SU/F90	WSC 8-SU/F90
External dimensions W x D x H (mm)	2170 x 2950 x 2840	3000 x 2950 x 2840	4000 x 2950 x 2840	5000 x 2950 x 2840	6000 x 2950 x 2840	7000 x 2950 x 2840	8000 x 2950 x 2840
Internal dimensions W x D x H (mm)	1930 x 2550 x 2520	2750 x 2550 x 2520	3750 x 2550 x 2520	4750 x 2550 x 2520	5750 x 2550 x 2520	6750 x 2550 x 2520	7750 x 2550 x 2520
Sump capacity (l)	700	1000	1400	1800	2 x 1100	2 x 1300	2 x 1500
Max. load (kg/m ²)	1000	1000	1000	1000	1000	1000	1000
Article no. door W x H (mm) 1250 x 2000 (SD)*	C64-4050-B	C64-4052-B	C64-4054-B	C64-4056-B	C64-4058-B	C64-4060-B	C64-4062-B
Article no. door W x H (mm) 1750 x 2000 (DD)**	C64-4051-B	C64-4053-B	C64-4055-B	C64-4057-B	C64-4059-B	C64-4061-B	C64-4063-B

* SD = single door ** DD = double door