

UMWELTSCHRÄNKE BAUHÖHE 1000 / 1950 MM
**Zur Lagerung von wassergefährdenden Gefahrstoffen
in Kleingebinden im Gebäude**

- ◆ Korpus aus Qualitätsstahlblech in einwandiger Bauweise mit hochwertiger Pulverbeschichtung RAL 7035 - lichtgrau, Tür/en RAL 1018 - zinkgelb
- ◆ Tür/en verstärkt, mit Griffzylinderschloss
- ◆ Höhenverstellbare Ebenen
- ◆ Lüftungsöffnungen in der/den Tür/en
- ◆ Bauhöhe 1000 standardmäßig mit 2 Lagerebenen
- ◆ Bauhöhe 1950 standardmäßig mit 4 Lagerebenen
- ◆ Auffangwanne (AW) aus 3 mm Stahlblech, verzinkt entsprechend AwSV - **Ü-Zeichen gemäß StawaR**
- ◆ Wannböden (WB), verzinkt, flüssigkeitsdicht verschweißt, Tragkraft 50 kg

store LAB
by LAGOM

MVV T8 Nr. C2.15.12
Stahlwannenrichtlinie
TÜV Nord Systems
DIBt Berlin

TÜV NORD
TÜV Nord Systems
Fachbetrieb nach AwSV
tuenord.de

**UWS 5/19 P,
Artikel-Nr. B80-6582-A**

**UWS 10/10 P,
Artikel-Nr. B80-6583-A**

**UWS 10/19 P,
Artikel-Nr. B80-6584-A**

**UWS 5/19 P,
Artikel-Nr. B80-6582-A**

**UWS 10/10 P, Artikel-Nr. B80-6583-A,
mit optionalem Lochblecheinsatz
für Auffangwanne und Wannböden**

**UWS 10/10 P,
Artikel-Nr. B80-6583-A**

**UWS 10/19 P, Artikel-Nr. B80-6584-A,
mit optionalem Lochblecheinsatz
für Auffangwanne und Wannböden**

Schranksyp	UWS 5/19 P	UWS 10/10 P	UWS 10/19 P
Außenmaße B x T x H in mm	500 x 500 x 1950	1000 x 500 x 1000	1000 x 500 x 1950
Innenmaße B x T x H in mm	495 x 475 x 1825	995 x 475 x 875	995 x 475 x 1825
Ausführung	1-türig	2-türig	2-türig
Auffangvolumen in Liter	AW 1 x 20 / WB 3 x 20	AW 1 x 30 / WB 1 x 20	AW 1 x 30 / WB 3 x 20
Gewicht in kg	54	49	78
Artikel-Nr., Außenkorpus RAL 7035 - lichtgrau, Tür/en RAL 1018 - zinkgelb	B80-6582-A	B80-6583-A	B80-6584-A

Zubehör	Artikel-Nr.	Artikel-Nr.	Artikel-Nr.
Zusätzlicher Wannböden, Stahlblech, verzinkt	B80-6558-A	B80-6559-A	B80-6559-A
Lochblecheinsatz für Auffangwanne AW	B80-6585-A	B80-6587-A	B80-6587-A
Lochblecheinsatz für Wannböden WB	B80-6586-A	B80-6588-A	B80-6588-A



ENVIRONMENTAL CABINETS HEIGHT 1000 / 1950 MM

For the storage of water-endangering hazardous substances in small packaging's in buildings

- ◆ Single-wall body made from high-quality powder-coated sheet steel in RAL 7035 - light grey, door(s) in RAL 1018 - zinc yellow
- ◆ Reinforced door(s), with cylinder handle lock
- ◆ Height-adjustable levels
- ◆ Ventilation slots in the door(s)
- ◆ Height 1000 mm with 2 storage levels as standard
- ◆ Height 1950 mm with 4 storage levels as standard
- ◆ Marking according to ASR A1.3
- ◆ **With inner fittings:**
 - Base sump tray (AW) made from 3 mm sheet steel, galvanized according to AwSV - **Ü-sign according to StawaR**
 - Tray-shaped shelves (WB), galvanized, are welded liquid-tight, load capacity 50 kg

storeLAB
by LAGOM



UWS 5/19 P,
Article no. B80-6582-A



UWS 10/10 P,
Article no. B80-6583-A



UWS 10/19 P,
Article no. B80-6584-A



UWS 5/19 P,
Article no. B80-6582-A



UWS 10/10 P, Article no. B80-6583-A,
with optional perforated cover plate
for base sump tray and tray-shaped shelf



UWS 10/10 P,
Article no. B80-6583-A



UWS 10/19 P, Article no. B80-6583-A,
with optional perforated cover plate
for base sump tray and tray-shaped shelves

Model	UWS 5/19 P	UWS 10/10 P	UWS 10/19 P
External dimensions W x D x H (mm)	500 x 500 x 1950	1000 x 500 x 1000	1000 x 500 x 1950
Internal dimensions W x D x H (mm)	495 x 475 x 1825	995 x 475 x 875	995 x 475 x 1825
Version	1-door	2-door	2-door
Sump capacity (l)	AW 1 x 20 / WB 3 x 20	AW 1 x 30 / WB 1 x 20	AW 1 x 30 / WB 3 x 20
Weight (kg)	54	49	78
Article no., outer body RAL 7035 - light grey, door(s) RAL 1018 - zinc yellow	B80-6582-A	B80-6583-A	B80-6584-A

Accessories	Article no.	Article no.	Article no.
Additional tray-shaped shelf, sheet steel, galvanized	B80-6558-A	B80-6559-A	B80-6559-A
Perforated cover plate for base sump tray AW	B80-6585-A	B80-6587-A	B80-6587-A
Perforated cover plate for tray-shaped shelf WB	B80-6586-A	B80-6588-A	B80-6588-A