



UMWELT-HÄNGESCHRÄNKE

Zur Lagerung von wassergefährdenden Gefahrstoffen in Kleingebinden im Gebäude

- ◆ Korpus aus Qualitätsstahlblech in einwandiger Bauweise mit hochwertiger Pulverbeschichtung RAL 7035 - lichtgrau, Tür/en RAL 1018 - zinkgelb
- ◆ Tür/en verstärkt oder Tür/en verstärkt mit Plexiglasausschnitt, über Zylinderschloss abschließbar
- ◆ Höhenverstellbarer Fachboden
- ◆ **Ausstattung:**
 - 1 x Auffangwanne (AW) aus 3 mm Stahlblech, verzinkt entsprechend AwSV - **Ü-Zeichen gemäß StawaR**
 - 1 x Fachboden (FB), pulverbeschichtet RAL 7035 - lichtgrau, höhenverstellbar
- ◆ Traglast 25 kg / Schrank
- ◆ Platzsparend am Arbeitsplatz montierbar
- ◆ Inkl. Montagematerial



UWS-H 800 GL, Artikel-Nr. B80-6592-A und
UWS-H 800, Artikel-Nr. B80-6590-A



UWS-H 400 GL, Artikel-Nr. B80-6591-A und
UWS-H 400, Artikel-Nr. B80-6589-A



UWS-H 800,
Artikel-Nr. B80-6590-A



UWS-H 400,
Artikel-Nr. B80-6589-A



UWS-H 800,
Artikel-Nr. B80-6590-A



UWS-H 400 GL,
Artikel-Nr. B80-6591-A



UWS-H 800 GL,
Artikel-Nr. B80-6592-A

Schranks typ	UWS-H 400	UWS-H 800	UWS-H 400 GL	UWS-H 800 GL
Außenmaße B x T x H in mm	400 x 300 x 600	800 x 300 x 600	400 x 300 x 600	800 x 300 x 600
Innenmaße B x T x H in mm	395 x 275 x 595	795 x 275 x 595	395 x 275 x 595	795 x 275 x 595
Auffangvolumen in Liter	5	10	5	10
Flügeltüren	1 (DIN rechts)	2	1 (DIN rechts, Plexiglastür)	2 (Plexiglastüren)
Gewicht in kg	12	22	12	22
Artikel-Nr., Außenkorpus RAL 7035 - lichtgrau, Tür/en RAL 1018 - zinkgelb	B80-6589-A	B80-6590-A	B80-6591-A	B80-6592-A



Explanations see practical informations on page 9 and 90!

ENVIRONMENTAL WALL CABINETS

For the storage of water-endangering hazardous substances in small packages in buildings.

- ◆ Single-wall body made from high-quality powder-coated sheet steel in RAL 7035 - light grey, door(s) in RAL 1018 - zinc yellow
- ◆ Reinforced door(s) with or without acrylic glass window, lockable via cylinder lock
- ◆ Height-adjustable levels
- ◆ **With inner fittings:**
 - Base sump tray (AW) made from 3 mm sheet steel, galvanized according to AwSV - **Ü-sign according to StawaR**
 - Tray-shaped shelf (WB), powder-coated RAL 7035 - light grey, height-adjustable
- ◆ Load capacity 25 kg per cabinet
- ◆ Space-saving installation at the workplace
- ◆ Mounting material included



UWS-H 800 GL, Article no. B80-6592-A and UWS-H 800, Article no.. B80-6590-A



UWS-H 400 GL, Article no. B80-6591-A and UWS-H 400, Article no. B80-6589-A



UWS-H 800, Article no. B80-6590-A



UWS-H 400, Article no. B80-6589-A



UWS-H 800, Article no. B80-6590-A



UWS-H 400 GL, Article no. B80-6591-A



UWS-H 800 GL, Article no. B80-6592-A

Model	UWS-H 400	UWS-H 800	UWS-H 400 GL	UWS-H 800 GL
External dimensions W x D x H (mm)	400 x 300 x 600	800 x 300 x 600	400 x 300 x 600	800 x 300 x 600
Internal dimensions W x D x H (mm)	395 x 275 x 595	795 x 275 x 595	395 x 275 x 595	795 x 275 x 595
Sump capacity (l)	5	10	5	10
Wing door(s)	1 (DIN right)	2	1 (DIN right, acrylic glass door)	2 (acrylic glass doors)
Weight (kg)	12	22	12	22
Article no., outer body RAL 7035 - light grey, door(s) RAL 1018 - zinc yellow	B80-6589-A	B80-6590-A	B80-6591-A	B80-6592-A