



SIS TYP 30 / 1200 NACH DIN EN 14470-1 (TYP 30)

Zugelassen zur eingeschränkten Lagerung von entzündbaren Flüssigkeiten am Arbeitsplatz nach DIN EN 14470-1 (Typ 30) und TRGS 510, Anhang 1

- ◆ Geprüfte und zugelassene Gesamtkonstruktion durch anerkannte Materialprüfanstalt nach DIN EN 14470-1 (Typ 30) mit einer Feuerwiderstandsfähigkeit von >30 Minuten
- ◆ Schrankkorpus aus B1-Material in RAL 7035 - lichtgrau, Türen in RAL 7035 - lichtgrau oder RAL 1007 - narzissengelb
- ◆ Einlegeböden im Raster von 32 mm höhenverstellbar
- ◆ Im Brandfall automatische Selbstschließung über Thermomechanik
 - Türen bei Temperaturanstieg auf < 50°C und
 - Zu- und Abluftkanäle bei Temperaturanstieg auf 70°C (±10°C)
- ◆ Lüftungsanschluss durch Rohrstutzen DN 80
- ◆ Betrieb gem. TRGS 510 (auch ohne Abluft zugelassen!)
- ◆ Erdungsanschluss entsprechend TRBS 2153 (Vermeidung von Zündquellen)
- ◆ Kennzeichnung nach DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- ◆ Nivellierfüße zum Ausgleich von Bodenunebenheiten
- ◆ Türen über Zylinderschloss abschließbar

Sicherheitsschränke mit Komplettausstattung:

- ◆ 1 x Bodenwanne (Auffangvolumen 33 Liter) entsprechend AwSV - **Ü-Zeichen gemäß StawaR**
- ◆ 1 x Lochblechabdeckung als 1. Lagerebene
- ◆ 3 x Einlegeboden
- ◆ **Türfeststellanlage**



SIS Typ 30/1200, Artikel-Nr. B80-2604-A, Türen RAL 1007 - narzissengelb, inkl. 3 Einlegeböden, Bodenwanne und Lochblechabdeckung



SIS Typ 30/1200, Artikel-Nr. B80-2600-A, Türen RAL 7035 - lichtgrau, inkl. 3 Einlegeböden, Bodenwanne und Lochblechabdeckung



Bodenwanne mit Lochblechabdeckung



Inkl. Sockel, mit abnehmbarer Blende

Schrankschranktyp		SIS Typ 30 / 1200
Außenmaße B x T x H in mm		1195 x 595 x 1935
Innenmaße B x T x H in mm		1075 x 515 x 1600
Flügeltüren		2
Gewicht in kg		225
Außenkorpus: RAL 7035 - lichtgrau		Werkstoff Innenausstattung
Artikel-Nr., Türen: RAL 7035 - lichtgrau	Stahlblech	B80-2600-A
Artikel-Nr., Türen: RAL 1007 - narzissengelb	Stahlblech	B80-2604-A

Zubehör	Material	Artikel-Nr.
Einlegeboden	Stahlblech	B80-2610-A



HAZARDOUS SUBSTANCES CABINETS (TYPE 30)



SIS TYPE 30 / 1200 AS PER DIN EN 14470-1 (TYPE 30)

Approved for the restricted storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 30) and TRGS 510, annex 1

- ◆ Whole construction tested and approved by an authorized materials testing institute as per DIN EN 14470-1 (type 30) with a fire resistance >30 minutes
- ◆ Body made from B1 material RAL 7035 - light grey, doors either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ◆ Height-adjustable shelves at intervals of 32 mm
- ◆ Automatic thermal closing mechanism if fire occurs
 - Door after temperature increase to $\leq 50^{\circ}\text{C}$ and
 - Inlet and outlet channels after temperature increase to 70°C ($\pm 10^{\circ}\text{C}$)
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRGS 510 (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- ◆ Markings according to DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- ◆ Leveling feet for installing cabinet horizontally
- ◆ Doors with cylinder lock

With inner fittings:

- ◆ 1 x base sump tray (sump capacity 33 liters) as per AwSV - **Ü-sign according to StawaR**
- ◆ 1 x perforated base tray cover as 1st storing level
- ◆ 3 x shelves
- ◆ **door hold-open device**



storeLAB



SIS Type 30/1200, Article no. B80-2604-A, doors RAL 1007 - daffodil yellow, incl. 3 shelves, base sump tray and perforated cover plate



SIS Type 30/1200, Article no. B80-2600-A, doors RAL 7035 - light grey, incl. 3 shelves, base sump tray and perforated cover plate



Base sump tray with perforated cover plate



Socle included, with removable panel

Model		SIS Type 30 / 1200
External dimensions W x D x H (mm)		1195 x 595 x 1935
Internal dimensions W x D x H (mm)		1075 x 515 x 1600
Doors		2
Weight (kg)		225
Outer body: RAL 7035 - light grey		Material inner fittings
Article no., doors: RAL 7035 - light grey		sheet steel B80-2600-A
Article no., doors: RAL 1007 - daffodil yellow		sheet steel B80-2604-A

Accessories	Material	Article no.
Shelf	sheet steel	B80-2610-A