



TYP 30 / 1200 KL - KOMBILAB NACH DIN EN 14470-1 (TYP 30)


Zugelassen zur Lagerung entzündbarer Flüssigkeiten am Arbeitsplatz nach DIN EN 14470-1 (Typ 30) und TRGS 510, Anhang 1, giftigen und sehr giftigen Stoffen, Säuren und Laugen. Ideale Kombination zur Lagerung verschiedenster Gefahrstoffe auf kleinstem Raum.

1 Sicherheitsschrank

- ◆ Geprüfte und zugelassene Gesamtkonstruktion durch anerkannte Materialprüfanstalt nach DIN EN 14470-1 (Typ 30) mit einer Feuerwiderstandsfähigkeit von >30 Minuten
- ◆ Schrankkorpus aus B1- Material in RAL 7035 - lichtgrau, Tür in RAL 7035 - lichtgrau oder RAL 1007 - narzissengelb
- ◆ Einlegeböden im Raster von 32 mm höhenverstellbar
- ◆ Lüftungsanschluss durch Rohrstützen DN 80
- ◆ Betrieb gem. TRGS 510 (auch ohne Abluft zugelassen!)
- ◆ Erdungsanschluss entsprechend TRBS 2153 (Vermeidung von Zündquellen)
- ◆ Kennzeichnung nach DIN EN 14470-1 / TRGS 510
- ◆ Tür über Zylinderschloss abschließbar
- ◆ Türanschlag standardmäßig DIN rechts



Typ 30 / 1200 KL6 GL, Artikel-Nr. B80-2617-A



Typ 30 / 1200 KL4, Artikel-Nr. B80-2612-A

Inkl. Inneneinrichtung:

1 Sicherheitsschrank (Typ 30) für entzündbare Flüssigkeiten nach DIN EN 14470-1

- 1 x Bodenwanne (Auffangvolumen 22 Liter) entsprechend WHG - **Ü-Zeichen gemäß StawaR**
- 1 x Lochblechabdeckung als 1. Lagerebene
- 2 x Einlegeböden
- Im Brandfall mit automatischer Selbstschließung über Thermomechanik
 - Tür bei Temperaturanstieg auf $\leq 50^{\circ}\text{C}$ und
 - Zu- und Abluftkanäle bei Temperaturanstieg auf $70^{\circ}\text{C} (\pm 10^{\circ}\text{C})$

- Türfeststellanlage

2 Lagerschrank für Säuren und Laugen

- 2 x 2 oder 2 x 3 Auszugswannen, Werkstoff PE, weiß

3 Giftfach mit Plexiglastür

- Zwischenboden

4 Montageblende Höhe 110 mm

- RAL 7035 - lichtgrau



Abluftventilatoren finden Sie auf Seite 138!

Schranktyp	Typ 30 / 1200 KL4	Typ 30 / 1200 KL5	Typ 30 / 1200 KL6 GL
Außenmaße* B x T x H in mm	1195 x 600 x 1935	1195 x 600 x 1935	1195 x 600 x 1935
Flügeltüren	4	4	4
Ausführung Säure-/Laugenschrank	Auszugsböden	6	6
	nutzbare Innenhöhe in mm	4 x 275 / 2 x 248	4 x 275 / 2 x 248
Gewicht in kg	251	257	257
Außenkorpus: RAL 7035 - lichtgrau	Werkstoff Innenausstattung		
Artikel-Nr., Tür Sicherheitsschrank (Typ 30): RAL 7035 - lichtgrau	Stahlblech	B80-2612-A	B80-2613-A
Artikel-Nr., Tür Sicherheitsschrank (Typ 30): RAL 1007 - narzissengelb	Stahlblech	B80-2615-A	B80-2616-A

* zzgl. Blende: Höhe 110 mm




TYPE 30 / 1200 KL - KOMBILAB AS PER DIN EN 14470-1 (TYPE 30)

Approved for the storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 30) and TRGS 510, annex 1, toxic and very toxic substances, acids and alkalis. Ideal combination for storage of various hazardous substances in a very small space.

1 Safety cabinet

- ◆ Whole construction tested and approved by an authorized materials testing institute as per DIN EN 14470-1 (type 30) with a fire resistance >30 minutes
- ◆ Body made from B1 material RAL 7035 - light grey, doors either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ◆ Height-adjustable shelves at intervals of 32 mm
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRGS 510 (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- ◆ Markings according to DIN EN 14470-1 / TRGS 510
- ◆ Leveling feet for installing cabinet horizontally
- ◆ Door with cylinder lock
- ◆ Door hinged right as standard



Type 30 / 1200 KL4,
Article no. B80-2612-A



Type 30 / 1200 KL6 GL,
Article no. B80-2617-A

With inner fittings:

1 Safety cabinet (type 30) for flammable liquids as per DIN EN 14470-1

- 1 x base sump tray (sump capacity 23 liters) as per WHG - Ü-sign according to StawaR
- 1 x perforated base tray cover as 1st storing level
- 2 x shelf
- Automatic thermal closing mechanism if fire occurs
 - Door after temperature increase $\leq 50^{\circ}\text{C}$ and
 - Inlet and outlet channels after temperature increase to 70°C ($\pm 10^{\circ}\text{C}$)

- door hold-open device

2 Storage cabinet for acids and alkalis

- 2 x 2 or 2 x 3 pull-out tray-shaped shelves, made from white PE

3 Poison compartment with acrylic glass door

- Dividing shelf

4 Cover panel made from HPL-coated sheets in RAL 7035 - light grey



Extraction fans
please see
page 136!

Model	Type 30 / 1200 KL4	Type 30 / 1200 KL5	Type 30 / 1200 KL6 GL
External dimensions* W x D x H (mm)	1195 x 600 x 1935	1195 x 600 x 1935	1195 x 600 x 1935
Doors	4	4	4
Design of acid / alkali cabinet	pull-out shelves	6	6
	usable inner height (mm)	4 x 275 / 2 x 248	4 x 275 / 2 x 248
Weight (kg)	251	257	257
Outer body: RAL 7035 - light grey	Material inner fittings		
Article no., door safety cabinet (type 30): RAL 7035 - light grey	sheet steel	B80-2612-A	B80-2613-A
Article no., door safety cabinet (type 30): RAL 1007 - daffodil yellow	sheet steel	B80-2615-A	B80-2616-A
		B80-2614-A	B80-2617-A

* plus cover panel: height 110 mm