



DACH-, SEITEN- UND RÜCKWÄNDE IN F90 - AUSFÜHRUNG

- ◆ Zur vorschriftsmäßigen Außenlagerung von Druckgasflaschen nach TRGS 510
- ◆ Dach und Wände in feuerbeständiger Ausführung nach DIN 4102
- ◆ Kragarmfachteiler mit Kettensicherung (ausklappbar)
- ◆ Die Anlieferung erfolgt in montiertem Zustand
- ◆ Gitterflügeltür abschließbar
- ◆ Je nach Ausführung mit Flügel- oder Doppelflügeltür

Komplett montierte Anlieferung!



Aufstellung direkt am Gebäude ohne Sicherheitsabstand

GFL-F90-6.08, Artikel-Nr. C66-2010-A



GFL-F90-24.21, Artikel-Nr. C66-2014-A, mit optionaler Trennwand



GFL-F90 mit geschlossener F90-Tür (für alle Typen erhältlich, Preise auf Anfrage)



GFL-F90 in Sonderausführung

Typenbezeichnung	GFL-F90-6.08	GFL-F90-8.11	GFL-F90-12.11	GFL-F90-16.21	GFL-F90-24.21	GFL-F90-32.21
Außenmaße B x T x H in mm	1120 x 1270 x 2310	1370 x 1270 x 2310	1370 x 1420 x 2310	2390 x 1270 x 2310	2390 x 1420 x 2310	2390 x 1620 x 2310
Innenmaße B x T x H in mm	800 x 920 x 2000	1050 x 920 x 2000	1050 x 1080 x 2000	2050 x 920 x 2000	2050 x 1080 x 2000	2050 x 1230 x 2000
Türausführung	Einflügelige Tür DIN rechts	Einflügelige Tür DIN rechts	Einflügelige Tür DIN rechts	Doppelflügeltür	Doppelflügeltür	Doppelflügeltür
Kapazität Gasflaschen ø 220 mm	6	8	12	16	24	32
Artikel-Nr., lackiert, ohne Bodengruppe	C66-2000-A	C66-2001-A	C66-2002-A	C66-2003-A	C66-2004-A	C66-2005-A
Artikel-Nr., lackiert, mit Bodengruppe	C66-2010-A	C66-2011-A	C66-2012-A	C66-2013-A	C66-2014-A	C66-2015-A

Zubehör	Artikel-Nr.
Auffahrrampe, verzinkt	C66-2020-A
Trennwand Tiefe 920 mm: GFL-F90-6.08/-8.11/-16.21	C66-2021-A
Trennwand Tiefe 1080 mm: GFL-F90-12.11/-24.21	C66-2022-A
Trennwand Tiefe 1230 mm: GFL-F90-32.21	C66-2023-A



Explanations see practical informations on page 6 and 84!

ROOF, SIDEWALLS AND BACK WALLS IN F90 VERSION

- ◆ For regular storage outdoors of pressurized gas cylinders in accordance with TRGS 510
- ◆ Roof and walls in fire-resistant version as per DIN 4102
- ◆ Cantilever arm compartment divider with safety chains (fold out)
- ◆ Mounted delivery
- ◆ Lockable grilled door
- ◆ With hinged or double-hinged door depending on version

Delivered fully assembled!



Installation directly next to building without safety distance!

GFL-F90-6.08, Article no. C66-2010-A



GFL-F90-24.21, Article no. C66-2014-A, with optional partition wall



GFL-F90 with closed door (available for all types, price on request)



GFL-F90 in special design

Model	GFL-F90-6.08	GFL-F90-8.11	GFL-F90-12.11	GFL-F90-16.21	GFL-F90-24.21	GFL-F90-32.21
External dimensions W x D x H (mm)	1120 x 1270 x 2310	1370 x 1270 x 2310	1370 x 1420 x 2310	2390 x 1270 x 2310	2390 x 1420 x 2310	2390 x 1620 x 2310
Internal dimensions W x D x H (mm)	800 x 920 x 2000	1050 x 920 x 2000	1050 x 1080 x 2000	2050 x 920 x 2000	2050 x 1080 x 2000	2050 x 1230 x 2000
Door version	Hinged door DIN right	Hinged door DIN right	Hinged door DIN right	Double-hinged door	Double-hinged door	Double-hinged door
Capacity, gas cylinders ø 220 mm	6	8	12	16	24	32
Article no., painted, without base group	C66-2000-A	C66-2001-A	C66-2002-A	C66-2003-A	C66-2004-A	C66-2005-A
Article no., painted, with base group	C66-2010-A	C66-2011-A	C66-2012-A	C66-2013-A	C66-2014-A	C66-2015-A

Accessories	Article no.
Ramp, galvanized	C66-2020-A
Partition wall depth 920 mm: GFL-F90-6.08/-8.11/-16.21	C66-2021-A
Partition wall depth 1080 mm: GFL-F90-12.11/-24.21	C66-2022-A
Partition wall depth 1230 mm: GFL-F90-32.21	C66-2023-A