




LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR FASSLAGERUNG

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ Zur Fasslagerung mit einflügeliger Tür zur Innen- und Außenaufstellung geeignet
- ◆ Stahlauffangwanne nach AwsV komplett mit Gitterrostabdeckung
- ◆ Tür selbstschließend
- ◆ Lackierung RAL 7035 - lichtgrau
- ◆ Umfangreiches Zubehör



WSC-Fass 4/F90,
Artikel-Nr. C64-4002-B



BRANDVERHALTEN

- Im Brandfall werden die Tür, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststellanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen



- Ex-geschützte Abluftüberwachung mit Signalhupe
- Türhalteanlage



K-90 Absperrvorrichtung



Optionale Außenbeleuchtung

Typenbezeichnung	WSC-Fass 2/F90	WSC-Fass 4/F90
Außenmaße B x T x H in mm	1720 x 1540 x 2325	1720 x 1840 x 2325
Innenmaße B x T x H in mm	1360 x 950 x 1900	1360 x 1250 x 1900
Auffangvolumen in Liter	220	220
Kapazität à 200-Liter-Fässer	2 auf Europalette	4 auf Chemiepalette
Artikel-Nr.,		
Tür B x H in mm = 1350 x 2000 (EF)	C64-4001-B	C64-4002-B

Zubehör	Artikel- Nr.
Ex-geschützte technische Zwangsentlüftung	C64-3116-A
LED-Leuchte Ex-Zone II, 230 V, 15 W, Leuchtenlichtstrom 2170 Lumen	H61-9131-A
Ex-geschützte Heizung 2 kW	C64-3103-A
Feststellanlage für einflügelige Tür	C64-3106-A
Schaltkasten	C64-3114-A
Potentialausgleich	C64-3113-A
Ex-geschützte Abluftüberwachung mit Signalhupe	C64-3109-A
zusätzliche Schallgeber-Blitzleuchtenkombination	C64-3110-A



Ex-geschützter Abluftventilator
inkl. Abluftüberwachung




FIRE PROTECTION CONTAINER F90 STEEL



LACONT FIRE PROTECTION CONTAINER FOR DRUM STORAGE

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ For the storage of drums with one-winged door
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey
- ◆ Wide range of accessories



WSC-Fass 4/F90,
Article no. C64-4002-B



FIRE BEHAVIOR

- If fire occurs the door, door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process



- Ex-proof exhaust air monitoring with signal horn
- Door hold-open device



K-90 shut-off device



Optional external lighting

Model	WSC-Fass 2/F90	WSC-Fass 4/F90
External dimensions W x D x H (mm)	1720 x 1540 x 2325	1720 x 1840 x 2325
Internal dimensions W x D x H (mm)	1360 x 950 x 1900	1360 x 1250 x 1900
Sump capacity (l)	220	220
Capacity, 200 liter drum	2 on Euro pallet	4 on chemical pallet
Article no., door W x H (mm) = 1350 x 2000 (SD)	C64-4001-B	C64-4002-B

Accessories	Article no.
Ex-proof forced ventilation	C64-3116-A
LED Lamp ex-zone II, 230 V, 15 W, effective luminous flux 2170 lm	H61-9131-A
Ex-proof heating 2 kW	C64-3103-A
Door hold-open device for single door	C64-3106-A
Switch box	C64-3114-A
Potential equalizing bar	C64-3113-A
Ex-proof exhaust air monitoring with signal horn	C64-3109-A
Combination of flashing light and sound generator	C64-3110-A



Ex-proof exhaust fan
incl. exhaust air monitoring