

LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR KTC-LAGERUNG

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ Zur KTC-Lagerung mit ein- oder zweiflügeliger Tür zur Innen- und Außenaufstellung geeignet
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Tür/en selbstschließend
- ◆ Lackierung RAL 7035 - lichtgrau
- ◆ Umfangreiches Zubehör



WSC-KTC 2/F90,
Artikel-Nr. C64-4004-B



BRANDVERHALTEN

- Im Brandfall werden die Türen, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststellanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen

Typenbezeichnung	WSC-KTC 1/F90	WSC-KTC 2/F90
Außenmaße B x T x H* in mm	1730 x 1840 x 2665	3270 x 1770 x 2480
Innenmaße B x T x H in mm	1360 x 1260 x 1900	2900 x 1300 x 1900
Auffangvolumen in Liter	1000	1000
Kapazität à KTC	1	2
Artikel-Nr., Tür B x H in mm = 1350 x 2000 (EF)	C64-4003-B	-
Artikel-Nr., Tür B x H in mm = 2900 x 2000 (DF)	-	C64-4004-B

* Außenmaße zuzüglich Fußplatten

Zubehör	Artikel- Nr.
Ex-geschützte technische Zwangsentlüftung	C64-3116-A
LED-Leuchte Ex-Zone II, 230 V, 15 W, Leuchtenlichtstrom 2170 Lumen	H61-9131-A
Ex-geschützte Heizung 2 kW	C64-3103-A
Feststellanlage für einflügelige Tür	C64-3106-A
Feststellanlage für zweiflügelige Tür	C64-3107-A
Schaltkasten	C64-3114-A
Potentialausgleich	C64-3113-A
Ex-geschützte Abluftüberwachung mit Signalhupe	C64-3109-A
zusätzliche Schallgeber-Blitzleuchtenkombination	C64-3110-A



WSC-KTC 1/F90,
Artikel-Nr. C64-4003-B



LACONT FIRE PROTECTION CONTAINER FOR KTC/IBC STORAGE

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ For the storage of KTC with one- or two-winged door(s),
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey
- ◆ Wide range of accessories



WSC-KTC 2/F90,
Article no. C64-4004-B



FIRE BEHAVIOR

- If fire occurs the door(s), door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process

Model	WSC-KTC 1/F90	WSC-KTC 2/F90
External dimensions W x D x H* (mm)	1730 x 1840 x 2665	3270 x 1770 x 2480
Internal dimensions W x D x H (mm)	1360 x 1260 x 1900	2900 x 1300 x 1900
Sump capacity (l)	1000	1000
Capacity, KTC/IBC	1	2
Article no., door W x H (mm) = 1350 x 2000 (SD)	C64-4003-B	-
Article no., door W x H (mm) = 2900 x 2000 (DD)	-	C64-4004-B

* External dimensions plus base plates

Accessories	Article no.
Ex-proof forced ventilation	C64-3116-A
LED Lamp ex-zone II, 230 V, 15 W, effective luminous flux 2170 lm	H61-9131-A
Ex-proof heating, 2 kW	C64-3103-A
Door hold-open device for single door	C64-3106-A
Door hold-open device for double door	C64-3107-A
Switch box	C64-3114-A
Potential equalizing bar	C64-3113-A
Ex-proof exhaust air monitoring with signal horn	C64-3109-A
Combination of flashing light and sound generator	C64-3110-A



WSC-KTC 1/F90,
Article no. C64-4003-B