



LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR PALETTENLAGERUNG MIT FLÜGELTÜREN

Diese Typenreihe ist speziell zur Einlagerung von Euro- oder Chemiepaletten sowie KTC/IBC geeignet. Bei Ausführung mit einer Türfeststelleinrichtung können die Türen im Arbeitsprozess offen gehalten werden. Somit kann der Brandschutzcontainer problemlos von einer Person bedient werden.

Ausstattung:

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ **Geeignet zur Innen- und Außenaufstellung**
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Türen selbstschließend
- ◆ Lackierung RAL 5015 - himmelblau



WSC-T-E.2-30 DF/F90,
Artikel-Nr. C64-3001-A
in Sonderfarbe



Zur Realisierung der optimalen Lagerbedingung steht ein umfangreiches Zubehör zur Auswahl, wie technische Belüftung, Beleuchtung, Heizung, Kühlung, Türfeststellanlage, Brandmeldung!



WSC-T-E.2-54 DF/F90,
Artikel-Nr. C64-3004-A



BRANDVERHALTEN

- Im Brandfall werden die Türen, Türritzen, Zu- und Abluftöffnung hermetisch abgeschlossen
- Ausführung mit Türfeststellanlage erlaubt es, die Türen im Arbeitsprozess geöffnet zu lassen



Abluftkanal mit K-90 Absperrvorrichtung

Typenbezeichnung	WSC-T-E.2-27 DF/F90	WSC-T-E.2-30 DF/F90	WSC-T-E.2-54 DF/F90	WSC-T-E.2-60 DF/F90
Außenmaße B x T x H* in mm	3070 x 1800 x 3700	3370 x 1800 x 3280	6140 x 1800 x 3700	6740 x 1800 x 3280
Fachmaße B x T x H** in mm	2700 x 1300 x 1400	3000 x 1300 x 1250	2700 x 1300 x 1400	3000 x 1300 x 1250
Anzahl der Lagerebenen	2	2	2	2
Auffangvolumen in Liter	1000	650	2 x 1000	2 x 650
Belastung in kg/m²	1500	1000	1500	1000
Kapazität 200-Liter-Fässer auf Europalette / auf Chemiepalette	12 / 16	12 / 16	24 / 32	24 / 32
Kapazität 1000-Liter-KTC/IBC	4	-	8	-
Tür B x H in mm (Baurichtmaß)	2700 x 3000	3000 x 2700	2 x 2700 x 3000	2 x 3000 x 2700
Artikel-Nr.	C64-3000-A	C64-3001-A	C64-3004-A	C64-3005-A

* Außenmaße zuzüglich Fußplatten

** Fachmaße und angegebene Kapazität ohne Berücksichtigung von elektrischen Einbauten (Lüftung, Heizung, usw.)



LACONT FIRE PROTECTION CONTAINER FOR PALLET STORAGE WITH DOUBLE DOORS

This series is particularly suitable for storing goods on euro- or chemical pallets or KTC/IBC. The Thermolock system allows the doors to be left open during the work process. Therefore the BSC can be used by one person without any problems.

Execution:

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey or RAL 5015 - sky blue



In order to realize the optimum storage conditions a wide range of accessories is available such as technical forced ventilation, lighting, heating, cooling system, door hold-open device, fire warning device!



WSC-T-E.2-30 DF/F90,
Article no. C64-3001-A



WSC-T-E.2-54 DF/F90,
Article no. C64-3004-A



FIRE BEHAVIOR

- If fire occurs the doors, door gaps, air in- and outlet slots are sealed hermetically
- In versions with Thermolock system doors can be left open during the work process



Air exhaust duct with K-90 shut-off device

Model	WSC-T-E.2-27 DF/F90	WSC-T-E.2-30 DF/F90	WSC-T-E.2-54 DF/F90	WSC-T-E.2-60 DF/F90
External dimensions W x D x H* (mm)	3070 x 1800 x 3700	3370 x 1800 x 3280	6140 x 1800 x 3700	6740 x 1800 x 3280
Compartment dimensions W x D x H** (mm)	2700 x 1300 x 1400	3000 x 1300 x 1250	2700 x 1300 x 1400	3000 x 1300 x 1250
Number of storage levels	2	2	2	2
Sump capacity (l)	1000	650	2 x 1000	2 x 650
Max. load (kg/m²)	1500	1000	1500	1000
Capacity, 200 liter drums on euro- / chemical pallets	12 / 16	12 / 16	24 / 32	24 / 32
Capacity, KTCs/IBCs	4	-	8	-
Door W x H (mm) (basic dimensions)	2700 x 3000	3000 x 2700	2 x 2700 x 3000	2 x 3000 x 2700
Article no.	C64-3000-A	C64-3001-A	C64-3004-A	C64-3005-A

* External dimensions plus base plates

** Compartment dimensions and stated capacities without considering electrical installations (ventilation, heating, etc.)