




LACONT FIRE-SAFETY-BRANDSCHUTZCONTAINER ZUR PALETTENLAGERUNG MIT SCHIEBETÜREN

Durch den Einsatz von Schiebetüren reduziert sich der Platzbedarf des Brandschutzlagers nur auf die Grundfläche des Containers. Zusätzliche und teure Lagerfläche wird nicht benötigt und kann anderweitig genutzt werden.

Ausstattung:

- ◆ Brandschutzcontainer mit Bauteilen nach Euronorm DIN EN 13501 (EI 90)
- ◆ **Geeignet zur Innen- und Außenaufstellung**
- ◆ Stahlauffangwanne nach AwSV komplett mit Gitterrostabdeckung
- ◆ Türen im Brandfall selbstschließend
- ◆ Lackierung RAL 5015 - himmelblau



BRANDVERHALTEN

- Im Brandfall werden die Türen automatisch geschlossen
- Türen, Türritzen, Zu- und Abluftöffnung werden hermetisch abgeschlossen



WSC-T-E.2-70 ST/F90,
Artikel-Nr. C64-3012-A



Schaltschrank mit
zentraler Steuerung
und Bedienelementen



Mit Brandschutzgutachten



Zur Realisierung der optimalen Lagerbedingung steht ein umfangreiches Zubehör zur Auswahl, wie technische Belüftung, Beleuchtung, Heizung, Kühlung, Brandmeldung!



WSC-T-E.2-80 ST/F90,
Artikel-Nr. C64-3013-A, in Sonderfarbe

Typenbezeichnung	WSC-T-E.2-70 ST/F90	WSC-T-E.2-80 ST/F90
Außenmaße B x T x H* in mm	7740 x 1900 x 3700	8480 x 1900 x 3700
Fachmaße B x T x H** in mm	3380 x 1300 x 1465	3900 x 1300 x 1500
Anzahl der Lagerebenen	2	2
Auffangvolumen in Liter	2 x 1000	2 x 1000
Belastung in kg/m ²	1500	1500
Kapazität 200-Liter-Fässer auf Europalette / auf Chemiepalette	24 / 32	32 / 48
Kapazität 1000-Liter-KTC/IBC	12	12
Anzahl der Schiebetüren	2	2
Artikel-Nr.	C64-3012-A	C64-3013-A

* Außenmaße zuzüglich Fußplatten

** Fachmaße und angegebene Kapazität ohne Berücksichtigung von elektrischen Einbauten (Lüftung, Heizung, usw.)



LACONT FIRE PROTECTION CONTAINER FOR PALLET STORAGE WITH SLIDING DOORS

The use of sliding doors reduces the space requirement of the fire protection store to the base area of the container only. Additional and expensive storage space is not required and can be used for other purposes.

Execution:

- ◆ Fire protection container with components according to DIN EN 13501 (EI 90)
- ◆ **Suitable for indoor and outdoor use**
- ◆ Steel sumps as per AwSV with grid cover
- ◆ Doors close automatically if fire occurs
- ◆ Outer body painted in RAL 7035 - light grey or RAL 5015 - sky blue



FIRE BEHAVIOR

- If a fire occurs the doors close automatically
- Doors, door gaps, air in- and outlet slots are sealed hermetically



WSC-T-E.2-70 ST/F90,
Article no. C64-3012-A



Control cabinet with
central control and
operating elements



With a fire
protection certificate



In order to realize the optimum storage conditions a wide range of accessories is available such as technical forced ventilation, lighting, heating, cooling system, door hold-open device, fire warning device!



WSC-T-E.2-80 ST/F90,
Article no. C64-3013-A, in special color

Model	WSC-T-E.2-70 ST/F90	WSC-T-E.2-80 ST/F90
External dimensions W x D x H* (mm)	7740 x 1900 x 3700	8480 x 1900 x 3700
Compartment dimensions W x D x H** (mm)	3380 x 1300 x 1465	3900 x 1300 x 1500
Number of storage levels	2	2
Sump capacity (l)	2 x 1000	2 x 1000
Max. load (kg/m²)	1500	1500
Capacity, 200 liter drums on euro- / chemical pallets	24 / 32	32 / 48
Capacity, 1000 liter KTCs/IBCs	12	12
Number of sliding doors	2	2
Article no.	C64-3012-A	C64-3013-A

* External dimensions plus base plates

** Compartment dimensions and stated capacities without considering electrical installations (ventilation, heating, etc.)